

This device is a WiFi based Video Intercom / Access Controller and RFID reader all contained in a tough, anti-vandal weatherproof housing.

Users can install the mobile app (TuyaSmart or Smartlife) to easily access the door with their smartphone.

The app supports 500 mobile users and can manage up to 1000 users.

## FEATURES

- Video calling via WiFi
- Full duplex voice intercom.
- Tough anti-vandal waterproof (IP65) housing.
- 1,000 users (990 common + 10 visitors)
- Card block enrolment
- PIN length: 4-6 digits
- Reads 125KHz EM cards & tags
- Pulse mode, Latch mode
- Relay
- Wiegand 26-44 bits input & output
- Low temperature resistance (-30°C)

## APPLICATIONS

- Access Control
- Time & Attendance
- ID Authentication

## SPECIFICATIONS

<b>Model</b>	CPVControl4-R
<b>User Capacity</b>	1000 (990 Common Users + 10 Visitors)
<b>Operating Voltage</b>	12 ~ 18V DC ( ≤150mA)
<b>Standby Current</b>	≤60mA
<b>Frequency</b>	125kHz
<b>Card Type</b>	125kHz EM
<b>Read Range</b>	2-6cm
<b>PIN Length</b>	4-6 digits
<b>Wiring Connections</b>	Relay Output, Exit Button, Wiegand Input/Output
<b>Relay</b>	One (NO, NC, Common)
<b>Adjustable Relay Time</b>	0-99 Seconds (5 seconds default)
<b>Lock Output Load</b>	2 Amp Maximum
<b>Wiegand Interface</b>	Wiegand 26/44 bits input & output
<b>Operating Temperature</b>	-40°C ~ 60°C (-40°F ~ 140°F)
<b>Operating Humidity</b>	0% ~ 92% RH
<b>Physical</b>	Zinc-Alloy
<b>Color</b>	Silver & Black
<b>Index of Protection</b>	IP65
<b>Dimensions</b>	142 x 48 x 22mm
<b>Unit Weight</b>	410g



### Video Calling, Remote Access & Management

Remote unlock, manage users  
and view activity log  
via Tuya or SmartLife apps